



TPE20 SERIES

0.35W EE20-6.1 - 50/60Hz PCB Mount Transformer

FEATURES

- It is miniaturised to be easily PCB mounted.
- It has very high insulation of 4000Vrms Hi-pot.
- It accords with UL94V-0 flammability requirements.
- Heat-resistance reaches 130°C

OPTIONS

- Packaging unit: 50 pieces
- Bulk packaging is standard
- Custom design available

APPLICATIONS

- Medical equipments
- Industrial equipments
- Industrial controls
- Test equipment
- Industrial computers
- Avionics & telecom

Part Number	Primary (V)	Secondary (V/mA)	No-Load (V)	Fig.
TPE200601	230	6 / 58.0	10.8	1
TPE200602	230	9 / 39.0	16.5	1
TPE200603	230	12 / 29.0	21.9	1
TPE200604	230	15 / 23.0	27	1
TPE200605	230	18 / 19.0	31.5	1
TPE200606	230	24 / 14.0	41.7	1
TPE200607	230	2 x 6 / 29.0	2 x 10.95	2
TPE200608	230	2x9/19.0	2 x 15.60	2
TPE200609	230	2 x 12 / 14.0	2 x 20.70	2
TPE200610	230	2 x 15 / 12.0	2 x 26.00	2
TPE200611	230	2 x 18 / 9.5	2 x 31.20	2
TPE200612	230	2 x 24 / 7.0	2 x 41.90	2

Part Number	Primary (V)	Secondary (V/mA)	No-Load (V)	Fig.
TPE200613	115	6 / 58.0	10.8	1
TPE200614	115	9 / 39.0	16.5	1
TPE200615	115	12 / 29.0	21.9	1
TPE200616	115	15 / 23.0	27	1
TPE200617	115	18 / 19.0	31.5	1
TPE200618	115	24 / 14.0	41.7	1
TPE200619	115	2 x 6 / 29.0	2 x 10.95	2
TPE200620	115	2x9/19.0	2 x 15.60	2
TPE200621	115	2 x 12 / 14.0	2 x 20.70	2
TPE200622	115	2 x 15 / 12.0	2 x 26.00	2
TPE200623	115	2 x 18 / 9.5	2 x 31.20	2
TPE200624	115	2 x 24 / 7.0	2 x 41.90	2

- Frequency 50/60Hz
- Split-bobbin
- Short-circuit-proof
- Potted under vacuum
- Temperature class to 70°C/B
- Weight: 0.024kg

