



EI SERIES

Low Frequency Power Transformer

FEATURES

- Single or Dual Primary)115/230V)
- Designed to meet International Safety Requirements
- Inherently Limited Versions available
- UL94V-0 Rated materials
- 4500 Vrms Isolation Strength(Pri:Sec)
- Designed for EN60950,UL1477 and UL1581
- Class B Insulation

Lamination (mm)	Stack (mm)	Model No	Volume (VA)	Distance Between Pins(mm)		Array Pitch (mm) ±0.5mm	Overall Dimension (mm)a*b*c ±0.5mm
				N*E	N*F		
EI24	8	EI24-1-X	0.4-0.5	3*4.8	3*4.8	15	26*22*22
EI-28	11	EI28-1-X	0.5-1.0	2*7.0	3*5.0	20	29*28*26
	12	EI28-2-X	1.0-1.5	4*4.9	4*4.9	20	29*28*26
	12	EI28-2A-X	0.8-1.5	2*7.5	3*5.0	22	29*28*28.1
	15	EI28-3-X	1.5-2.0	4*4.9	4*4.9	20	29*28*30
	18	EI28-4-X	2.0-3.0	4*4.9	4*4.9	20	29*28*32
EI-30	10.5	EI30-1-X	1.0-1.5	4*5.0	4*5.0	20	31*26*20
	15	EI30-2-X	2.0-2.5	4*5.0	4*5.0	20	31*26*25
	18	EI30-3-X	2.5-3.0	4*5.0	4*5.0	20	31*26*28
	22	EI30-4-X	3.5-4.0	4*5.0	4*5.0	20	31*26*31
EI-35	10	EI35-1-X	1.5-2.0	4*5.6	4*5.6	21.5	36*31*25.5
	12	EI35-2-X	1.0-2.0	2*7.5	3*5.0	22.1	36*31*31
	12	EI35-2A-X	1.0-2.0	2*7.5	5+4.8+5	21.8	36*31*31
	13.5	EI35-3-X	2.0-2.5	3*6.3	3*6.6	29.9	36*31*32
	14	EI35-4-X	1.0-2.0	4*5.0	4*5.0	23.4	36*31*32.5
	14.5	EI35-5-X	2.0-3.0	3*6.0	4*4.5	21.1	36*31*35
	15	EI35-6-X	3.0-4.0	4*5.6	4*5.6	21.7	36*31*32
	15	EI35-6A-X	2.0-3.0	2*7.5	3*6.0	22	36*31*32
	15	EI35-6B-X	3.0-4.0	4*5.0	4*5.0	21	36*31*32
	18	EI35-7-X	4.0-5.0	4*4.7	4*4.7	22.5	36*31*38
	18	EI35-7A-X	4.0-5.0	4*5.0	4*5.0	21.5	36*31*34
	20	EI35-8-X	4.0-5.5	4*5.6	4*5.6	21.7	36*31*37
20	EI35-8A-X	5.0-5.5	4*5.0	4*5.0	23	36*31*37	
EI-41	10	EI41-1-X	2.0-3.0	2*9.1	2*9.1	23.7	42*34*25
	13	EI41-2-X	4.0-5.0	5*6.35	5.08+4*6.35	25	42*34*30
	15	EI41-3-X	4.0-5.0	5*4.9	5*4.9	25	42*34*30
	15.5	EI41-4-X	3.5-4.5	5.3+2*4.5+5.3	5.3+2*4.5+5.3	23	42*34*40
	16	EI41-5-X	4.0-5.0	4*5.0	4*5.0	25	42*34*30

