



TPE3015 SERIES

2W EI30-15.5 - 50/60Hz PCB Mount Transformer

FEATURES

- Vacuum filling
- Two compartments bobbins
- Self-extinguishing plastics UL 94 VO
- Degree of protection IP 00
- 100 grams weight

OPTIONS

- Bulk packaging is standard
- Custom design available

APPLICATIONS

- Medical equipments
- Industrial equipments
- Industrial controls
- Test equipment
- Industrial computers
- Avionics & telecom

PRIMARY VOLTAGE: 230					
Part Number	Secondary V	Secondary mA	No-load V	Amb. Temp. °C	Rating VA
TPE301521	6	333	10,4	T70B	2
TPE301522	9	222	15,5	T70B	2
TPE301523	12	167	20,7	T70B	2
TPE301524	15	133	25,8	T70B	2
TPE301525	18	111	30,8	T70B	2
TPE301526	24	83	41,4	T70B	2
TPE301527	2 x 6	2 x 167	2 x 10.4	T70B	2
TPE301528	2 x 9	2 x 111	2 x 15.4	T70B	2
TPE301529	2 x 12	2 x 83	2 x 20.7	T70B	2
TPE301530	2 x 15	2 x 67	2 x 25.8	T70B	2
TPE301531"	2 x 18	2 x 56	2 x 30.8	T70B	2
TPE301532"	2 x 24	2 x 42	2 x 41.4	T70B	2

PRIMARY VOLTAGE: 115					
Part Number	Secondary V	Secondary mA	No-load V	Amb. Temp. °C	Rating VA
TPE301533	6	333	10,4	T70B	2
TPE301534	9	222	15,5	T70B	2
TPE301535	12	167	20,7	T70B	2
TPE301536	15	133	25,8	T70B	2
TPE301537	18	111	30,8	T70B	2
TPE301538	24	83	41,4	T70B	2
TPE301539	2 x 6	2 x 167	2 x 10.4	T70B	2
TPE301540	2 x 9	2 x 111	2 x 15.4	T70B	2
TPE301541	2 x 12	2 x 83	2 x 20.7	T70B	2
TPE301542	2 x 15	2 x 67	2 x 25.8	T70B	2
TPE301543	2 x 18	2 x 56	2 x 30.8	T70B	2
TPE301544	2 x 24	2 x 42	2 x 41.4	T70B	2

* To be noted : 2 x 18 V and 2 x 24 non safety transformer approved, conform to EN 61558-2-6 (Isolating transformer).

- Resin class B CEI 85 (20 000 h testing to CEI 126)
- Inherently short-circuits proof transformer
- 30 V model is VDE EN 61558-2-6 certified (production on request)
- Insulation voltage 4 KV
- 100% tested production
- Certification : CCA procedure on request

